



## Standard Operating Procedure Refuse Disposal Division



### Landfill Operations **Dust Control**

1. The water truck must spray the roads with **reclaimed** water periodically throughout the day. Water must also be sprayed at the fill face and dumping pad whenever dust occurs.
2. On windy days, keep excavation of cover material with low moisture content to a minimum by wetting the cut area.  
**\*Note** – The fines pile is always moist.
3. Place dusty loads at the toe of the face of the trash and bridge over as quickly as possible.
4. Chemical treatments may be used to maintain semi-permanent access and haul roads to prevent excessive dust. The Engineering staff will designate which chemicals may be used.

***Environmental Management System (EMS) – ISO 14001***

***Process Map #: DO-1.2***

#### **Benefit of Compliance to Instruction:**

- Ensures good neighbor relations
- Creates a cleaner, safer work atmosphere
- Ensures compliance with Regulatory requirements
- Helps maintain a positive public image

#### **Consequence of Non-Compliance to Instruction:**

- Violations and fines from APCD
- Impact to flight operations at MCAS Miramar
- Degraded air quality in and around Miramar Landfill
- Disciplinary action

---

**Reviewed by:** Mark zu Hone, *EMR*  
**Approved by:** Gary Gobel, *Greens Processing Supervisor*  
Rory Clay, *Landfill Senior Civil Engineer*

Date: June 1, 2001

*The on-line version and secured hardcopy are the controlled documents. The secured hardcopy will be identified by a "Controlled Copy" stamp (in red) and RDD Deputy Director signature. Any other documents are uncontrolled. Verify revision level status on-line or contact the EMR*